



## Rib Lath

FLAMCO's 3/8" Hi-Rib Lath is a rigid metal lath that has solid ribs running the length of each sheet. This lath is used in 3-coat stucco and thin veneer stone installations. Hi-Rib is primarily used in ceiling and soffit applications and is installed both vertically and horizontally. All FLAMCO lath is produced from G60 hot-dipped galvanized steel.

## Packaging

Weight/ sq. yard	Finish	Sheet weight	Sheet size	Sheets/bundle	Bundles/Pallet	Pallet weight
3.4 lbs.	Galvanized	6.8 lbs.	27" x 97"	10	50	3400 lbs.

## ASTM & Code Standards

ASTM A653 (Galvanized Coating)

ASTM C841 (Interior Installation)

ASTM C1780 (Thin veneer stone installation)

ASTM C1063 (General Installation)

ASTM C847

ASTM A924

## LEED Points and Recycled Content

When you use FLAMCO metal lath products your project can earn points for:

LEED Credit MR 4.1/4.2 – Recycled Content Requirements (Applies to all projects)

LEED Credit MR 5.1/5.2 – Requirements (Applies to all projects)

## Support Spacing for 3/8" Hi-Rib Lath (adapted from ASTM C1063, table 3)

Type of Lath	Nominal Weight (per sq. yard)	Vertical Spacing (Inches)			Horizontal (Inches)	
		Wood Plaster(Metal)		Other(Metal)	Wood or Concrete	Metal
3/8" 7 Rib Lath	3.4 lbs.	24	24	24	24	24

ASTM C1063 allows framing for High Rib Lath to span up to 24" on Center. High Rib Lath is Installed with the nose of the ribs touching the framing members. For more detailed installation instructions refer to ASTM C1063.