

DIAMOND EXPANDED METAL LATH 2.5 LBS / SQ. YARD (GALVANIZED STEEL meeting ASTM C847)

This submittal covers carbon steel hot dip galvanized G-60 finish expanded metal flat diamond lath without paper backing and is designed to be used as a base for gypsum or portland cement plaster.

Permissible Variations Per ASTM C847

- | | |
|---|---|
| • Minimum thickness of expanded metal lath: | Diamond mesh expanded metal lath - $\frac{1}{8}$ inch |
| • Nominal sheet dimensions – inches | All styles – Length of Sheet: 97 inches (min)
All styles – Width of Sheet: 27 inches (min) |
| • Nominal weights for lath (US) lbs/yd ² | Flat Diamond Expanded Metal Lath 2.5 lbs/yd ² |
| • Permissible Variations in inches: | Thickness: $\pm 1/64$ inch
Width: $\pm 3/16$ inch
Length: -0 + 1 inch
Weight: $\pm 10\%$ |

Packaging and Markings

Metal Lath is packed 10 sheets per bundle and 25 bundles per lift. Each lift is marked with the manufacturer's name, style of lath, and lath weight.

Specification Standards

FLAMCO LATH AND STUCCO ACCESSORIES MEET THE FOLLOWING SPECIFICATIONS:

- ASTM C847 – Standard specification for expanded metal lath
- ASTM C1063 – Standard specification for installation of lathing and furring to receive interior and exterior portland cement based plaster
- ASTM A653 – Standard specification for steel sheet, zinc-coated (galvanized) by the hot-dip process



For More Information Contact:

Flamco Bead & Lath Inc.
(800) 634-3937

Jon Whaley
(904) 334-8110
jpwhaley@flamco.com