



**FLORIDA METAL PRODUCTS INC.
MANUFACTURERS OF QUALITY BUILDING PRODUCTS
RESIDENTIAL BUILDING PRODUCTS & MORE**

**FLAMCO MIDWEST PAINTED 12” ALUMINUM SOFFIT
SPECIFICATIONS AND DATA SHEET**

.016 PAINTED ALUMINUM (NOMINAL)
.019 PAINTED ALUMINUM (NOMINAL)

SUBSTRATE: 3105 H28 or 3105 H26

COATING SPECIFICATIONS

COATING: VALSPAR THERMOSETTING POLYESTER
GLOSS: 8-14 @ 60 DEGREES
FLEXIBILITY: 1-2T NO TAPE REMOVAL ON .019 ALUMINUM
(VARIES WITH THICKNESS)
PENCIL HARDNESS: F-2H
REVERSE IMPACT: 1.5M METAL THICKNESS
DRY FILM THICKNESS: .70-.80 MILS

NFOA SPECIFICATIONS

* CENTER VENT: 4.58
* FULL VENT: 13.74

* FLAMCO’s Center and Full Vent 12” Aluminum Soffit Panels are designed to provide air circulation in the attic area in order to reduce heat buildup and condensation. The Open Net Free Area can vary slightly from panel to panel.